



ENGINEERING & TECHNICAL DATA — Flexadux® TR L-Vac

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
4.72	.9	.024	N/A	3:1	13	N/A
5	.9	.030	N/A	3:1	18.5	N/A
5.51	1.1	.030	N/A	3:1	18	N/A
6.3	1.3	.030	N/A	3:1	16.3	N/A
7.09	1.7	.030	N/A	3:1	14	N/A
7.87	2	.030	N/A	3:1	13	N/A

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Medium weight polypropylene elastomer hose reinforced with both a plastic and a spring steel wire helix

Temperature Range: -20°F to 185°F

Standard Color: Orange

Standard Lengths: 10 Feet

- Lift Capacity: Single Tube – up to 300 lbs.
Dual Tubes – up to 650 lbs.
Triple Tubes – up to 1000 lbs.

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com

