



ENGINEERING & TECHNICAL DATA — Flexadux TR[®] E-2

| INSIDE DIAMETER (IN) | APPROX. WEIGHT (LBS/FT) | WALL THICKNESS (IN) | CL BEND RADIUS (IN) | COMPRESSION RATIO | NEGATIVE PRESSURE (IN/HG) | WORKING PRESSURE (PSI) |
|----------------------|-------------------------|---------------------|---------------------|-------------------|---------------------------|------------------------|
| 4 | .3 | .020 | 4 | 2:1 | 24 | 22 |
| 6 | .55 | .020 | 6 | 2:1 | 8 | 15 |

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Light weight polyethylene hose reinforced with a spring steel wire helix

Temperature Range: -40°F to 150°F

Standard Color: Clear

Standard Lengths: 25 Feet

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com

