



## ENGINEERING & TECHNICAL DATA — Flexadux<sup>®</sup> TR XLT

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
2	.14	.012	2	6:1	29	7
2.5	.17	.012	2.48	6:1	24	5.9
3	.21	.012	2.96	6:1	14	4.93
3.5	.25	.012	3.23	6:1	8.9	4.2
4	.28	.012	3.5	6:1	6	3.7
5	.35	.012	3.96	6:1	3	3
6	.42	.012	4.42	6:1	1.8	2.5

Technical data based on 2 ft. straight lengths of hose @ 72°

**Construction:** Very light weight thermoplastic rubber hose reinforced with a spring steel wire helix

**Temperature Range:** -60°F to 275°F

**Standard Color:** Black

**Standard Lengths:** 25 Feet

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464  
sales@flexaust.com • www.flexaust.com



A SCHAUBURG HOSE TECHNOLOGY COMPANY