



ENGINEERING & TECHNICAL DATA — Flexadux® T-7 White

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
2	.25	.030	1.75	2:1	29	14
3	.4	.030	2.5	2:1	29	10
4	.6	.030	3.5	2:1	15	7
5	.8	.030	4.5	2:1	13	6
6	.85	.030	5.5	2:1	8	5
8	1	.030	7	2:1	6	4
10	2	.030	8	2:1	8	3.5
12	2.7	.030	10	2:1	5	3

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Medium weight thermoplastic rubber hose reinforced with a spring steel wire helix

Temperature Range: -40°F to 250°F

Standard Color: White

Standard Lengths: 25 & 50 Feet

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com



A **SCHAUENBURG** HOSE TECHNOLOGY COMPANY