



## ENGINEERING & TECHNICAL DATA — Heat-Flex® Raceflex®

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
1.5	.18	N/A	1.8	3:1	29	30
2	.25	N/A	2	3:1	29	30
3	.32	N/A	2.5	3:1	29	30
4	.5	N/A	3	5:1	27	30
5	.59	N/A	3.5	5:1	14	30
6	.62	N/A	4	5:1	9	19

Technical data based on 2 ft. straight lengths of hose @ 72°

**Construction:** Light weight laminate of fiberglass & vacuum metallized polyester film

**Temperature Range:** -65°F to 625°F

**Standard Color:** Silver

**Standard Lengths:** 12 Feet

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

**Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464**  
**sales@flexaust.com • www.flexaust.com**

