



## ENGINEERING & TECHNICAL DATA – Bendway® Plus

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
3	.47	.006	13	N/A	29	18
4	.64	.006	15	N/A	29	15
5	.8	.006	17	N/A	29	13
5.5	.85	.006	19	N/A	29	12
6	.92	.006	24	N/A	29	11
7	1.06	.006	26	N/A	29	9.5
8	1.2	.006	28	N/A	29	8.5
9	1.38	.006	30	N/A	29	8
10	1.55	.006	32	N/A	29	6
11	1.69	.006	34	N/A	29	5.5
12	1.83	.006	37	N/A	29	5

Technical data based on 2 ft. straight lengths of hose @ 72°

**Construction:** Manufactured using 316Ti Stainless Steel in a patented roll lock construction

**Temperature Range:** up to 1650°F

**Standard Color:** Silver

**Standard Lengths:** 25 Feet (3\_ to 8\_), 15 Feet (9\_ to 12\_)

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464  
[sales@flexaust.com](mailto:sales@flexaust.com) • [www.flexaust.com](http://www.flexaust.com)



A SCHAUBENBURG HOSE TECHNOLOGY COMPANY