



ENGINEERING & TECHNICAL DATA — Flex-Lok® 600

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
3	.75	N/A	2.5	5:1	8	15
4	.85	N/A	3	5:1	7.2	13.6
5	.95	N/A	3.5	6:1	6.1	11
6	1	N/A	4.5	6:1	5	9.2
8	1.1	N/A	5	6:1	4	8.5
10	1.2	N/A	5.5	6:1	3.5	8
12	1.5	N/A	6	6:1	3.3	7.3

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Double-ply construction silicone coated fiberglass fabric hose with a heat-resistant fiberglass liner mechanically crimped in a continuous process

Temperature Range: -65°F to 600°F

Standard Color: Silver

Standard Lengths: 25 Feet

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com

