



ENGINEERING & TECHNICAL DATA — Flex-Lok® 1200

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
4	1.1	N/A	4	3:1	9	16
5	1.3	N/A	5	4:1	8	13.5
6	1.6	N/A	6	4:1	7	12
8	2.2	N/A	8	4:1	4	10
10	2.5	N/A	10	4:1	3.5	9.5
12	2.8	N/A	12	4:1	3	8
14	3.65	N/A	16	3:1	.5	1.5
16	4.3	N/A	16	3:1	.25	1
18	4.5	N/A	18	3:1	.2	.5

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Double-ply wire inserted fiberglass fabric hose mechanically crimped in a continuous process

Temperature Range: -40°F to 1200°F

Standard Color: Red

Standard Lengths: 25 Feet

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com



A **SCHAUENBURG** HOSE TECHNOLOGY COMPANY