



## ENGINEERING & TECHNICAL DATA — Dayflex® MG-V

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
.75	.11	N/A	.875	1.6:1	29	15
1	.15	N/A	1	1.6:1	29	15
1.25	.18	N/A	1.25	1.6:1	29	15
1.5	.23	N/A	1.625	1.6:1	29	15
1.75	.28	N/A	2	1.6:1	29	15
2	.35	N/A	2.3	1.6:1	29	15

Technical data based on 2 ft. straight lengths of hose @ 72°

**Construction:** PVC hose reinforced with a vinyl coated spring steel wire helix

**Temperature Range:** -10°F to 160°F

**Standard Color:** Gray

**Standard Lengths:** 50 Feet

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

**Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464**  
**sales@flexaust.com • www.flexaust.com**



A **SCHAUENBURG** HOSE TECHNOLOGY COMPANY