



ENGINEERING & TECHNICAL DATA — Flex-Tube® EF+

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
4	.5	.026	6	2:1	14	24
6	.8	.032	8	2:1	8	16
8	1.2	.032	10	2:1	6	14
10	1.5	.038	12	2:1	3	7

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Medium weight coextruded flexible EVA elastomer hose with a rigid external polypropylene helix

Temperature Range: -40°F to 200°F

Standard Color: Clear with Green Helix

Standard Lengths: 25 & 50 Feet

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com



A SCHAUBURG HOSE TECHNOLOGY COMPANY