



## ENGINEERING & TECHNICAL DATA — Flex-Tube® EF-FR

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
3	.4	.028	4	2:1	22	15
4	.45	.028	5	2:1	20	12
5	.7	.028	6	2:1	18	11
6	.9	.035	7	2:1	16	10
7	1.2	.035	8	2:1	13	9
8	1.5	.035	9.75	2:1	12	8
10	1.9	.040	11	2:1	6	7

Technical data based on 2 ft. straight lengths of hose @ 72°

**Construction:** Medium weight coextruded polyolefin elastomer hose with a rigid external polypropylene helix

**Temperature Range:** -20°F to 160°F, Intermittent to 200°F

**Standard Color:** Black with Black Helix (Custom Colors Available)

**Standard Lengths:** 25 Feet

- Manufactured with materials compliant with UL 94-V2

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

**Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464**  
**sales@flexaust.com • www.flexaust.com**

