



## ENGINEERING & TECHNICAL DATA — Dayflex® WL-V-20

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
1.25	.16	.020	1.25	2:1	29	30
1.5	.18	.020	1.5	2:1	29	30
2	.24	.020	2	2:1	25	25
2.5	.29	.020	2.5	2:1	20	15
3	.35	.020	3	2:1	20	15

Technical data based on 2 ft. straight lengths of hose @ 72°

**Construction:** PVC hose reinforced with a coated spring steel wire helix

**Temperature Range:** -20°F to 160°F

**Standard Color:** Black

**Standard Lengths:** 25 Feet

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464  
sales@flexaust.com • www.flexaust.com



A SCHAUBURG HOSE TECHNOLOGY COMPANY