



ENGINEERING & TECHNICAL DATA — Dayflex® Flex-Vac

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
1	.12	N/A	1	2:1	29	30
1.25	.18	N/A	1.25	2:1	29	22
1.5	.23	N/A	1.5	2:1	29	20
2	.35	N/A	2	2:1	29	19
2.5	.4	N/A	2.5	2:1	29	10
3	.5	N/A	3	2:1	29	8
4	.65	N/A	4	2:1	20	3

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: PVC hose reinforced with a vinyl coated spring steel wire helix and external yarn

Temperature Range: -10°F to 160°F

Standard Color: Gray

Standard Lengths: 50 Feet (1.25" to 2.5"), 25 Feet (3" to 4")

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com

