



ENGINEERING & TECHNICAL DATA — Flex-Tube® PU 60 GV-GW

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
2	.45	.050	4	N/A	28	50
2.5	.58	.050	5	N/A	28	50
3	.75	.055	6	N/A	25	45
4	1.1	.060	7	N/A	25	40
5	1.4	.060	9	N/A	20	30
6	1.63	.060	10	N/A	15	28
7	1.85	.060	11	N/A	6	25
8	2.13	.060	12	N/A	5	20

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Specially formulated static dissipative highly flexible very heavy weight polyurethane hose reinforced with a rigid external PVC helix & an embedded copper grounding wire

Temperature Range: -20°F to 160°F

Standard Color: Clear Wall with Black Helix

Standard Lengths: 25

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.

Tel: 574-267-7909 • Toll Free Tel: 800-343-0428 • Toll Free Fax: 800-382-8464
sales@flexaust.com • www.flexaust.com

